

Amendment Under 37 C.F.R. § 1.111
U.S. Application No.: 10/694,772

Atty Dkt No.: 71450.00009

AMENDMENTS TO THE CLAIMS:

1. (Currently Amended) A flexible wired circuit board having a plurality of layers formed in a generally rectangular, flat, strip-shape, and having a generally narrow central portion and relatively rectangular, flat, widened end portions, for temperature measurement, said layers comprising:

a conductor layer; and

~~a base insulating layer formed in a generally rectangular, flat, strip-shape, and having generally rectangular, flat, widened end portions, said base insulating layer being formed on one side of said conductor layer;~~

wherein the conductor layer is formed from a metal foil having a proportional relation between temperature and specific electric resistance;

wherein said conductor layer includes a temperature detecting portion formed when said conductor layer is formed as a wiring portion and arranged in a predetermined pattern on said base insulating layer; and

wherein the temperature detecting portion is formed on the base insulating layer at one of the generally rectangular, flat, widened end portions of the base insulating layer.

2. (Previously presented) The flexible wired circuit board for temperature measurement according to claim 1, wherein the conductor layer is a stainless foil.

3. (Previously presented) The flexible wired circuit board for temperature measurement according to claim 1, wherein said wiring portion includes a wiring folded in

Amendment Under 37 C.F.R. § 1.111
U.S. Application No.: 10/694,772

Atty Dkt No.: 71450.00009

such a continuous form that adjacent parts of the wiring extending in parallel are spaced apart from each other at a predetermined interval.

4. (Previously presented) The flexible wired circuit board for temperature measurement according to claim 3, wherein the wiring in the temperature detecting portion has an entire length of 50 mm or more.

5. (Previously presented) The flexible wired circuit board for temperature measurement according to claim 3, wherein the adjacent parts of the wiring in the temperature detecting portion are spaced apart from each other at a pitch of 100 μ m or more.

6-17. (Canceled)

18. (Currently amended) A flexible wired circuit board having a plurality of layers formed in a generally rectangular, flat, strip-shape, and having a generally narrow central portion and relatively rectangular, flat, widened end portions, for temperature measurement, said layers comprising:

a conductor layer formed from a stainless foil;

a base insulating layer formed from a polyimide film ~~and formed in a generally rectangular, flat, strip-shape, and having generally rectangular, flat, widened end portions,~~
~~said base insulating layer being formed on one side of said conductor layer;~~

a cover insulating layer formed from a polyimide film, and formed on another side of said conductor layer;

Amendment Under 37 C.F.R. § 1.111
U.S. Application No.: 10/694,772

Atty Dkt No.: 71450.00009

wherein said conductor layer, comprising a main wiring portion for wiring and a sensor-wiring portion, ~~for including a temperature detecting temperature portion~~, is formed in one piece in a form of a predetermined pattern; and

wherein the temperature detecting portion is formed on the base insulating layer at one of the generally rectangular, flat, widened end portions of the base insulating layer.